

PRV

PATENT- OCH REGISTRERINGSVERKET
Patentavdelningen

**Intyg
Certificate**

Härmed intygas att bifogade kopior överensstämmer med de handlingar som ursprungligen ingivits till Patent- och registreringsverket i nedannämnda ansökan.

This is to certify that the annexed is a true copy of the documents as originally filed with the Patent- and Registration Office in connection with the following patent application.



(71) Sökande *Micronic Laser Systems AB, Täby SE*
Applicant (s)

(21) Patentansökningsnummer *0201019-7*
Patent application number

(86) Ingivningsdatum *2002-04-04*
Date of filing

REC'D 15 MAY 2003

WIPO PCT

Stockholm, 2003-04-22

*För Patent- och registreringsverket
For the Patent- and Registration Office*

Sonia André
Sonia André

Avgift
Fee

PRIORITY DOCUMENT
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH
RULE 17.1(a) OR (b)

BEST AVAILABLE COPY

A MASK BLANK AND A METHOD FOR PRODUCING THE SAME

FIELD OF THE INVENTION

[0001] The present invention relates to a method for producing substrates, in particular it relates to a method for producing mask blanks or reticle blanks using said substrate. The invention also relates to a mask substrate and a reticle substrate.

BACKGROUND OF THE INVENTION

[0002] The problems that are solved by the invention are related to the difficulty of making sufficiently accurate and highly resolved masks. In particular it relates to the use of chemically amplified resist. Such chemically amplified resist (CAR) is used for mask making with DUV radiation (Micronic SIGMA 7100 at 248 nm and ETEC ALTA 4000 at 257 nm) and with electron beams (several suppliers). It has also been used for laser pattern generators at 364 nm (study published by DNP). The chemically amplified resist is used for several reasons: high sensitivity, high contrast and high transparency at short wavelengths.

[0003] Common problems related to CAR is its sensitivity to various delay times, from post-apply bake (PAB) to exposure, during exposure if the exposure is prolonged, as it may be in a mask pattern generator, and between exposure and post-exposure bake (PEB). Before PAB and after PEB it is generally regarded as stable. The sensitivity to variations in and extension of these delay times, causing changes in edge profiles and CD measures, is partly due to intrinsic and spontaneous reactions in the resist, partly to contamination from the ambient, and partly by reactions with other materials used in the mask blank, in particular the chrome itself.

[0004] Figure 1 shows a mask blank according to prior art. It has a substrate 101, usually quartz, but in reflecting EUV masks it can be any stable material, e.g. silicon or ultra-low expansion (ULE) glass or ceramic. The chrome 102 is covered with a partially anti-reflective layer 103 of, typically, chromium oxide or chromium nitride. The chromium is sputtered onto the quartz substrate and the AR coating is sputtered on top of it, forming a combined film with typically 70-100 nm thickness. The resist 104 is coated on top of the AR layers 103. Contamination from the ambient may be in the form of amines, ammonia or other nitrogen-containing compounds in ppb

concentrations. The process is also affected by oxygen and water in the atmosphere, but to a lesser degree, and different for different types of resist chemistries.

[0005] Moving to smaller dimensions one would want to use a thinner resist in order to avoid depth-of-focus loss and resist image collapse for small features with high aspect ratio. This has been addressed in another patent application, US 09/664,288, by the same inventor and included herein by reference. The companion application discloses a multi-layer pattern-transfer method to produce masks and similar products with extremely small features. This is likely to be used for reticles written with 157 nm light and with EUV. In a closer future a single-layer chemically amplified process with high stability and good line-width control is desirable. Such a process is described in the following.

[0006] It has been found that chemically amplified resists give less than perfect results when used on mask substrates, Figure 2. The reflectance of the chrome gives standing waves, depicted in figure 2 by the plurality of cavities 201 in the resist profile, and the chemical activity of the chrome oxide surface gives a foot 202 in the resist profile. Especially the foot is troublesome as a clean vertical sidewall is needed for good dimension control

SUMMARY OF THE INVENTION

[0007] Accordingly, it is an object of the present invention to provide a method of preparing a mask blank and a mask blank as such, which overcomes or at least reduces the above-mentioned problems.

[0008] This object, among others, is according to a first aspect of the invention attained by a method for manufacturing a mask blank comprising providing a substrate; forming a masking layer on said substrate; forming at least one layer of material on said substrate such that a reflectivity of a writing wavelength to a film sensitive to the writing wavelength is below 4 %.

[0009] In another embodiment according to the invention, said reflectivity is below 2%.

[0010] In another embodiment according to the invention, said reflectivity is below 1%.

[0011] In another embodiment according to the invention, said reflectivity is below 0.5 %.

[0012] In another embodiment according to the invention, a silicon compound is facing the film sensitive to the writing wavelength.

[0013] In another embodiment according to the invention a layer of silicon dioxide is facing the film sensitive to the writing wavelength.

5 [0014] In another embodiment according to the invention, the masking material comprises silicon.

[0015] In another embodiment according to the invention, said film sensitive to the writing wavelength is less than 300 nm thick.

10 [0016] In another embodiment according to the invention, said film sensitive to the writing wavelength is less than 200 nm thick.

[0017] In another embodiment according to the invention, said at least one layer of material comprises oxynitride.

15 [0018] In another embodiment said invention further comprising the actions of exposing at least a portion of said film sensitive to the writing wavelength with a writing wavelength and etching the exposed mask blank in a gas mixture comprising chlorine or fluorine.

[0019] In another embodiment according to the invention, the film sensitive to the writing wavelength is having low activation energy.

20 [0020] In another embodiment according tot the invention, the film sensitive to the writing wavelength is a chemically amplified resist (CAR).

[0021] In another said invention further comprising the actions of xposing at least a portion of said film sensitive to the writing wavelength with a writing wavelength and stopping the reaction in said film sensitive to the writing wavelength by exposure to a base.

25 [0022] In another embodiment said invention further comprising the action of slowing down a reaction caused by exposure by having an ambient gas of low humidity.

[0023] In another embodiment said invention further comprising the action of forming a film of adhesive promoter.

30 [0024] The invention also relates to a method for manufacturing a mask blank comprising the actions of providing a substrate; forming a masking layer on said substrate and forming at least one layer of material on said substrate such that a surface facing a film sensitive to a writing wavelength is chemically inert.

[0025] In another embodiment according to the invention, a reflectivity of said writing wavelength to said film sensitive to the writing wavelength is below 4 %.

[0026] In another embodiment according to the invention, said reflectivity is below 2 %.

5 [0027] In another embodiment according to the invention, said reflectivity is below 1 %.

[0028] In another embodiment according to the invention, said reflectivity is below 0.5 %.

10 [0029] In another embodiment according to the invention, a silicon compound is facing the film sensitive to the writing wavelength.

[0030] In another embodiment according to the invention, a layer of silicon dioxide is facing the film sensitive to the writing wavelength.

[0031] In another embodiment according to the invention, the masking material comprises silicon.

15 [0032] In another embodiment according to the invention, said film sensitive to the writing wavelength is less than 300 nm thick.

[0033] In another embodiment according to the invention, said film sensitive to the writing wavelength is less than 200 nm thick.

20 [0034] In another embodiment according to the invention, at least one layer of material comprises oxynitride.

[0035] In another embodiment said invention further comprising the action of exposing at least a portion of said film sensitive to the writing wavelength with a writing wavelength and etching the exposed mask blank in a gas mixture comprising chlorine. or fluorine.

25 [0036] In another embodiment according to the invention, the film sensitive to the writing wavelength is having low activation energy.

[0037] In another embodiment according to the invention, the film sensitive to the writing wavelength is a chemically amplified resist (CAR).

30 [0038] In another embodiment said invention further comprising the actions of exposing at least a portion of said film sensitive to the writing wavelength with a writing wavelength and stopping the reaction in said film sensitive to the writing wavelength by exposure to a base.

[0039] In another embodiment said invention further comprising the action of slowing down a reaction caused by exposure by having an ambient gas of low humidity.

5 [0040] The invention also relates to a mask blank comprising a substrate; a masking layer on said substrate and at least one layer of material on said substrate such that a reflectivity of a writing wavelength to a film sensitive to the writing wavelength is below 4 %.

[0041] In another embodiment of the invention, said reflectivity is below 2%.

[0042] In another embodiment of the invention, said reflectivity is below 1%.

10 [0043] In another embodiment according to the invention said reflectivity is below 0.5 %.

[0044] In another embodiment according to the invention, a silicon compound is facing the film sensitive to the writing wavelength.

15 [0045] In another embodiment according to the invention, a layer of silicon dioxide is facing the film sensitive to the writing wavelength.

[0046] In another embodiment according to the invention, the masking material comprises silicon.

[0047] In another embodiment according to the invention, said film sensitive to the writing wavelength is less than 300 nm thick.

20 [0048] In another embodiment according to the invention, said film sensitive to the writing wavelength is less than 200 nm thick.

[0049] In another embodiment according to the invention, said at least one layer of material comprises oxynitride.

25 [0050] In another embodiment according to the invention, the film sensitive to the writing wavelength is having low activation energy.

[0051] In another embodiment according to the invention, the film sensitive to the writing wavelength is a chemically amplified resist (CAR).

[0052] In another embodiment said invention further comprising a film of adhesive promoter.

30 [0053] The invention also relates to a mask blank comprising a substrate; a masking layer on said substrate and at least one layer of material on said substrate such that a surface facing a film sensitive to a writing wavelength is chemically inert.

P00135

[0054] In another embodiment of the invention, a reflectivity of said writing wavelength to said film sensitive to the writing wavelength is below 4%.

[0055] In another embodiment according to the invention, said reflectivity is below 2%.

5 [0056] In another embodiment according to the invention, said reflectivity is below 1%.

[0057] In another embodiment according to the invention, said reflectivity is below 0.5 %.

10 [0058] In another embodiment according to the invention, a silicon compound is facing the film sensitive to the writing wavelength.

[0059] In another embodiment according to the invention, a layer of silicon dioxide is facing the film sensitive to the writing wavelength.

[0060] In another embodiment according to the invention, the masking material comprises silicon.

15 [0061] In another embodiment according to the invention, said film sensitive to the writing wavelength is less than 300 nm thick.

[0062] In another embodiment according to the invention, said film sensitive to the writing wavelength is less than 200 nm thick.

20 [0063] In another embodiment according to the invention, said at least one layer of material comprises oxynitride.

[0064] In another embodiment according to the invention, the film sensitive to the writing wavelength is having low activation energy.

[0065] In another embodiment according to the invention the film sensitive to the writing wavelength is a chemically amplified resist (CAR).

25 [0066] In another embodiment said invention further comprising a film of adhesive promoter.

[0067] Further characteristics of the invention, and advantages thereof, will be evident from the detailed description of preferred embodiments of the present invention given hereinafter and the accompanying Figs. 1-7, which are given by way
30 of illustration only, and thus are not limitative of the present invention.

BRIEF DESCRIPTION OF THE DRAWINGS

- [0068] Figure 1 shows a photo-mask blank as known in the art with a quartz substrate, a coating consisting of layers of Cr, CrO_xN_y , and a resist.
- [0069] Figure 2 shows a typical resist profile as known in the art.
- 5 [0070] Figure 3 shows an embodiment of the invention with a quartz substrate, a coating comprising Cr, an anti-reflecting coating, a chemically inert top layer, and a resist.
- [0071] Figure 4 shows a typical resist profile produced by the invention.
- [0072] Figure 5 shows the diffusion of acid as encountered in the current art.
- 10 [0073] Figure 6 shows the diffusion of acid when using the inventive substrate/mask blank.
- [0074] Figure 7 shows a method for production of a mask blank.

DETAILED DESCRIPTION

- [0075] The following detailed description is made with reference to the figures.
- 15 Preferred embodiments are described to illustrate the present invention, not to limit its scope, which is defined by the claims. Those of ordinary skill in the art will recognize a variety of equivalent variations on the description that follows.
- [0076] The invention discloses an improved mask substrate with an improved anti-reflective coating having less chemical activity and/or better anti-reflective properties.
- 20 [0077] An embodiment of the invention is shown in Figure 3. The depicted embodiment has a substrate 301 and a mask layer 302, typically chrome, an anti-reflecting layer 303 and a chemically inert top layer 304 and a resist layer 305. The anti reflecting layer 303 and the chemically inert layer 304 may comprise one or a plurality of stacked layers. The top surface layer is devoid of chromium and comprises of a chemically inert material, e.g. silicon dioxide or silicon oxynitride. The stack of layers is optimized to give low reflectivity between the resist and the coating. When the resist is removed the reflectivity in air is approximately 6%. The low reflectivity between the stack and the resist removes the standing waves that are
- 25 formed in current art.
- 30 [0078] Current mask blanks have a reflectivity of 6% or more between the resist and the chrome stack, giving a periodic modulation of the local exposure dose of 2:1.

A post-exposure bake is used to remove the standing waves. This post-exposure is a critical process step and has to be controlled tightly in order not to introduce errors. The diffusion necessary to remove the standing waves does also affect process latitude in a negative way, especially for small features.

5 [0079] Within the general definition of the invention there are many possible configurations, which can be explored and optimized using commercial thin-film programs, e.g., the essential MacLeud. Experimental data for the materials and verification of the design can be obtained from measurements by ellipsometers (e.g. Sopra, Plasmos, Woolam) or reflectometers (Nanometrics, Perkin Elmers, BioRad, n&k).

10 [0080] Figure 4 depicts the resist profile using the inventive substrate/mask blank

[0081] Figure 5 shows a mechanism behind the resist profile in Figure 2. The exposing light 501 impinges on the resist 502 and creates acid 503. Partly spontaneously at room temperature and partly during post-exposure baking the acid molecules diffuse along random-walk paths 504 and activates ("de-protects") the chemically amplified resist so that it becomes soluble in the developer. The effect on the resist is proportional to the length of the diffusing paths. However, when an acid molecule touches the chromium oxide surface 505 it is either neutralized or just bound there 506 so that it does not continue to diffuse. The binding energy can be fairly small and still impede the free diffusion of the acid. The result is a depletion of acid described by an inverse diffusion gradient.

20 [0082] Figure 6 shows the same diffusion in the invention. The chemically inert top layer does not bind the acid and there is no depletion of acid. Therefore there is no foot.

25 [0083] The production of inventive mask blanks is similar to that currently used, but the exact recipe is different. The chrome and the anti-reflecting film stack are deposited by sputtering. A thin layer of SiO₂ is sputtered on top of the anti-reflecting film. The blank is treated with an adhesive promoter, e.g. HMDS, and the resist is spun on. The blank is then baked to drive out solvents and compact the resist film, inspected and shipped/stored until it is exposed.

30 [0084] Photo-masks have an optical density around 3 or at least above 2.5. Optical density is the logarithm of base 10 of the attenuation in transmission and optical density 3 means 0.001 transmission.

[0085] The following is a recipe that gives the desired result with a stack being 90 nm thick. The reflection between the resist and the coating is 0.8% and the optical density is 3.3.

[0086] Cr 0.85 - j 2.01, thickness 68 nm,

5 [0087] SiO_xN_y 2.12 - j 0.50, thickness 22 nm, where j is the imaginary part of the complex refractive index.

[0088] The following recipe has a top layer of stoichiometric SiO_2 to further improve the chemical inertness and reflectivity. It has a reflection of 0.3% and an optical density of 2.8.

10 [0089] Cr 0.85 - j 2.01, thickness 55 nm

[0090] SiO_xN_y 2.12 - j 0.50, thickness 22 nm

[0091] SiO_2 1.50, thickness 10 nm

[0092] A more oxidized surface layer can be obtained in the first recipe by treating the SiO_xN_y surface with an oxygen plasma.

15 [0093] Another recipe, which is closer to the currently used CrO_xN_y , has a reflectivity of 0.6% and an optical density of 3.0.

[0094] Cr 0.85 - j 2.01, thickness 60 nm

[0095] CrO_xN_y 2.12 - j 0.80, thickness 20 nm

[0096] SiO_2 1.50, thickness 10 nm

20 [0097] Both CrO_xN_y and SiO_xN_y can be made with varying properties and in the particular case the thickness and/or process parameters must be optimized empirically. The embodiments above are computed based on refractive indices found in the public domain. It is also possible to use other chemically inert compounds to create a chrome-free surface with good properties. Using silicon compounds does
25 have a number of benefits, though. The silicon surface chemistry is well known and adhesion promoters and other surface modifiers are well known and understood.

Several processes for producing films of SiO_2 and SiO_xN_y are available, including evaporation and sputtering, reactive evaporation and sputtering, CVD and plasma deposition. Silicon glasses have very good adhesion to chromium, either to metallic
30 chrome or to chrome oxides.

[0098] In a different embodiment the chrome is replace with silicon. Silicon has higher complex refractive index at 248 nm than Cr, therefore the stack is thinner than for Cr. Furthermore Si is easier to etch and has better dry etch selectivity vs. resist,

giving a more stable process and the possibility to use thinner resist. The following stack has 0.0% reflection and 2.7 optical density.

[0099] Si 1.69 - j 2.76, thickness 40 nm

[00100] CrO_xN_y 2.12 - j 0.80, thickness 27 nm

5 [00101] SiO_2 1.50, thickness 10 nm

[00102] The same materials will work for 193 nm, although the optimum thickness for the different layers may be slightly different.

[00103] The issue with the delay times in a mask-writer is that they are long and to some degree unpredictable. Optical pattern generators have a writing time that is
10 proportional to the covered area, but at some complexity level the system has to stop and wait for data, giving some unpredictability to the process.

[00104] For long writing times it is advantageous to use a low-activation energy resist, such as for instance a resist named 1100 provided by Clariant or a resist named KRS provided by IBM, where the de-protection of the resist happens spontaneously at
15 room temperature. This is generally accompanied by a diffusion of acid. A final PEB is not necessary for the de-protection but kills any remaining acid and causes diffusion that smoothes out standing waves. With mask blanks according to the present invention there are no or very little standing waves.

[00105] The diffusion of acid can be stopped either by the development or by a
20 stopping treatment where the blank is exposed to a high concentration of amines, ammonia or other bases. The simplest stop to the diffusion, however, is to develop the plate. There are several advantages of this: no baking removes one of the larger sources of CD variations, and also one of process bias. The spontaneous de-protection directly after exposure of any point on the surface reduces the influence of long delay
25 times.

[00106] Remaining acid causes diffusion and will give a delay-dependant CD error. However, it can be predicted beforehand and pre-compensated. The writing strategy is mentioned in said US application with application number 09/664,288 by the same inventor and gives a nearly constant CD effect, which can be corrected for
30 by dose or by manipulation of the data. In said method of exposing a reticle a plurality of exposure passes is used, where said exposure passes are made in a first and a second direction, the first and second directions being essentially opposed.

[00107] Some photo resist formulations need water present for the de-protection to take place. This is the reason why chemically amplified resists can be used in electron beam systems with write times of 24 hours or more. Using a dry atmosphere in an optical pattern generator operating in air slows down the de-protection during writing and reduces the delay effect as long as the blank is shielded from water. A dry atmosphere causes problems with charging and static electricity, and they must be handled and alleviated, e.g. with ionizers. The writer is purged with dried air. Load locks ensure that there is no ambient air coming into the enclosure.

[00108] A silicon-based film etches in plasma with chlorine present. This is the same chemistry as for etching chrome so both films can be etched in the same gas mixture. For all-silicon masks the etching can be optimized without regard to the chrome etch requirements.

[00109] For optical alignment of a chrome (or equivalent material) pattern to a second layer, it is important that there is a reflectance difference between the resist and the substrate on one side and the resist and the chrome stack on the other. The recipes given above give close to zero reflectivity only for DUV, so a non-actinic sensor will be useful. Inspection can be done at a different wavelength in transmission or reflection, but the low reflectivity can be a problem for inspection in reflection at wavelength

[00110] While the preceding examples are cast in terms of a method, devices and systems employing this method are easily understood. A magnetic memory containing a program capable of practicing the claimed method is one such device. A computer system having memory loaded with a program practicing the claimed method is another such device.

[00111] It will be obvious to a person to apply the invention to new situations, such as other wavelengths and materials. Reflecting reticles for EUV is an obvious application. Other masking materials than chrome may be used and the chemical inert layer could be based on other compounds than silicon compounds. An example is to use a diamond-like carbon film.

[00112] While the present invention is disclosed by reference to the preferred embodiments and examples detailed above, it is understood that these examples are intended in an illustrative rather than in a limiting sense. It is contemplated that modifications and combinations will readily occur to those skilled in the art, which

P00135

PRU-04-04

modifications and combinations will be within the spirit of the invention and the scope of the following claims.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2

CLAIMS

- 1 1. A method for manufacturing a mask blank comprising the actions of:
 - 2 - providing a substrate;
 - 3 - forming a masking layer on said substrate;
 - 4 - forming at least one layer of material on said substrate such that a reflectivity
 - 5 of a writing wavelength back into a film sensitive to the writing wavelength is
 - 6 below 4 %.
- 1 2. The method according to claim 1, wherein said reflectivity is below 2%.
- 1 3. The method according to claim 1, wherein said reflectivity is below 1%.
- 1 4. The method according to claim 1, wherein said reflectivity is below 0.5 %.
- 1 5. The method according to claim 1, wherein a silicon compound is facing the
- 2 film sensitive to the writing wavelength.
- 1 6. The method according to claim 1, wherein a layer of silicon dioxide is facing
- 2 the film sensitive to the writing wavelength.
- 1 7. The method according to claim 1, wherein the masking material comprises
- 2 silicon.
- 1 8. The method according to claim 1, wherein said film sensitive to the writing
- 2 wavelength is less than 300 nm thick.
- 1 9. The method according to claim 1, wherein said film sensitive to the writing
- 2 wavelength is less than 200 nm thick.
- 1 10. The method according to claim 1, wherein said at least one layer of material
- 2 comprises oxynitride.
- 1 11. The method according to claim 1, further comprising the action of:

- 2 - exposing at least a portion of said film sensitive to the writing
- 3 wavelength with a writing wavelength,
- 4 - etching the exposed mask blank in a gas mixture comprising chlorine.

1 **12.** The method according to claim 1, further comprising the action of:

- 2 - exposing at least a portion of said film sensitive to the writing
- 3 wavelength with a writing wavelength,
- 4 - etching the exposed mask blank in a gas mixture comprising fluorine.

1 **13.** The method according to claim 12, wherein the film sensitive to the writing
2 wavelength is having low activation energy;

1 **14.** The method according to claim 1, wherein the film sensitive to the writing
2 wavelength is a chemically amplified resist (CAR).

1 **15.** The method according to claim 1, further comprising the actions of:

- 2 - Exposing at least a portion of said film sensitive to the writing
- 3 wavelength with a writing wavelength,
- 4 - stopping the reaction in said film sensitive to the writing wavelength
- 5 by exposure to a base.

1 **16.** The method according to claim 12 or 15, further comprising the action of;

- 2 - slowing down a reaction caused by exposure by having an ambient gas of low
- 3 humidity.

1 **17.** The method according to claim 1, further comprising the action of;

- 2 - forming a film of adhesive promoter.

1 **18.** A method for manufacturing a mask blank comprising the actions of:

- 2 - providing a substrate;
- 3 - forming a masking layer on said substrate;

4 - forming at least one layer of material on said substrate such that a surface
5 facing a film sensitive to a writing wavelength is chemically inert.

1 19. The method according to claim 18, wherein a reflectivity of said writing
2 wavelength back into said film sensitive to the writing wavelength is below 4 %.

1 20. The method according to claim 18, wherein said reflectivity is below 2 %.

1 21. The method according to claim 18, wherein said reflectivity is below 1 %.

1 22. The method according to claim 18, wherein said reflectivity is below 0.5 %.

1 23. The method according to claim 18, wherein a silicon compound is facing the
2 film sensitive to the writing wavelength.

1 24. The method according to claim 18, wherein a layer of silicon dioxide is
2 facing the film sensitive to the writing wavelength.

1 25. The method according to claim 18, wherein the masking material comprises
2 silicon.

1 26. The method according to claim 18, wherein said film sensitive to the writing
2 wavelength is less than 300 nm thick.

1 27. The method according to claim 18, wherein said film sensitive to the writing
2 wavelength is less than 200 nm thick.

1 28. The method according to claim 18, wherein at least one layer of material
2 comprises oxynitride.

1 29. The method according to claim 18, further comprising the action of:

- 2 - Exposing at least a portion of said film sensitive to the writing
3 wavelength with a writing wavelength,
4 - etching the exposed mask blank in a gas mixture comprising chlorine.

1 30. The method according to claim 18, further comprising the action of:

- 2 - exposing at least a portion of said film sensitive to the writing
3 wavelength with a writing wavelength,
- 4 - etching the exposed mask blank in a gas mixture comprising fluorine.

1 31. The method according to claim 29, wherein the film sensitive to the writing
2 wavelength is having low activation energy.

1 32. The method according to claim 18, wherein the film sensitive to the writing
2 wavelength is a chemically amplified resist (CAR).

1 33. The method according to claim 32, further comprising the actions of:

- 2 - exposing at least a portion of said film sensitive to the writing
3 wavelength with a writing wavelength,
- 4 - stopping the reaction in said film sensitive to the writing wavelength
5 by exposure to a base.

1 34. The method according to claim 29 or 32, further comprising the action of;

- 2 - slowing down a reaction caused by exposure by having an ambient gas
3 of low humidity.

1 35. A mask blank comprising

- 2 - a substrate;
- 3 - a masking layer on said substrate;
- 4 - at least one layer of material on said substrate such that a reflectivity of a
5 writing wavelength back into a film sensitive to the writing wavelength is below
6 4 %.

1 36. The mask blank according to claim 35, wherein said reflectivity is below 2%.

1 37. The mask blank according to claim 35, wherein said reflectivity is below 1%.





1 38. The mask blank according to claim 35, wherein said reflectivity is below 0.5
2 %.

- 1 39. The mask blank according to claim 35, wherein a silicon compound is facing
2 the film sensitive to the writing wavelength.
- 1 40. The mask blank according to claim 35, wherein a layer of silicon dioxide is
2 facing the film sensitive to the writing wavelength.
- 1 41. The mask blank according to claim 35, wherein the masking material
2 comprises silicon.
- 1 42. The mask blank according to claim 35, wherein said film sensitive to the
2 writing wavelength is less than 300 nm thick.
- 1 43. The mask blank according to claim 35, wherein said film sensitive to the
2 writing wavelength is less than 200 nm thick.
- 1 44. The mask blank according to claim 35, wherein said at least one layer of
2 material comprises oxynitride
- 1 45. The mask blank according to claim 35, wherein the film sensitive to the writing
2 wavelength is having low activation energy.
- 1 46. The mask blank according to claim 35, wherein the film sensitive to the
2 writing wavelength is a chemically amplified resist (CAR).
- 1 47. The mask blank according to claim 35, further comprising;
2 - a film of adhesive promoter.
- 1 48. A mask blank comprising
2 - a substrate;
3 - a masking layer on said substrate;
4 - at least one layer of material on said substrate such that a surface facing a film
5 sensitive to a writing wavelength is chemically inert.

- 1 49. The mask blank according to claim 48, wherein a reflectivity of said writing
2 wavelength back into said film sensitive to the writing wavelength is below 4%.
- 1 50. The mask blank according to claim 48, wherein said reflectivity is below 2%.
- 1 51. The mask blank according to claim 48, wherein said reflectivity is below 1%.
- 1 52. The mask blank according to claim 48, wherein said reflectivity is below 0.5
2 %.
- 1 53. The mask blank according to claim 48, wherein a silicon compound is facing
2 the film sensitive to the writing wavelength.
- 1 54. The mask blank according to claim 48, wherein a layer of silicon dioxide is
2 facing the film sensitive to the writing wavelength.
- 1 55. The mask blank according to claim 48, wherein the masking material
2 comprises silicon.
- 1 56. The mask blank according to claim 48, wherein said film sensitive to the
2 writing wavelength is less than 300 nm thick.
- 1 57. The mask blank according to claim 48, wherein said film sensitive to the
2 writing wavelength is less than 200 nm thick.
- 1 58. The mask blank according to claim 48, wherein said at least one layer of
2 material comprises oxynitride
- 1 59. The mask blank according to claim 48, wherein the film sensitive to the writing
2 wavelength is having low activation energy.
- 1 60. The mask blank according to claim 48, wherein the film sensitive to the
2 writing wavelength is a chemically amplified resist (CAR).
- 1 61. The mask blank according to claim 48, further comprising;
2 a film of adhesive promoter.
3

ABSTRACT

An aspect of the present invention includes a method for manufacturing a mask blank. A substrate is provided. A masking layer is formed on said substrate. At least one layer of material is formed on said substrate such that a reflectivity of a writing wavelength to a film sensitive to the writing wavelength is below 4 %. Other aspects of the present invention are reflected in the detailed description, figures and claims.






Fig. 5




Fig. 6




Fig. 7